

# For Fast and Intuitive Digital Workflows

## Work Directly On Screen

The DTU-2231 combines a 21.5", 16:9 widescreen LCD with Wacom's patented, cordless, battery-free pen technology. Use the pen directly on the display surface to enjoy the benefits of an all-digital workflow while simulating a pen-on-paper experience. The full HD (1920 x 1080) interactive pen display is an optimal choice for people who use applications that benefit from working with pen directly on a large, wide-format screen. It can be utilized for redlining and signing documents, annotating and sharing presentations, completing forms, creating hand-drawn imagery, and capturing handwritten notes.



## Key Features

- 21.5" display with full HD (1920 x 1080) resolution.
- Built-in DVI-I pass-thru connector handles either digital or analog input and allows mirroring directly from pen display to a projector or another display.
- Internal scaler will take video input signals of different resolutions and display them in their native resolution and aspect ratio.
- Internal USB hub with two user-accessible USB ports to provide easy access to your favorite USB devices.
- Completely flat textured, anti-glare surface.
- Adjustable stand that allows for 15 to 72 degrees of incline.
- Pen that supports 512 levels of pressure-sensitivity on the pen tip. Also includes programmable side switches and an eraser.
- Display Toggle feature allows control and navigation of other monitors in a multiple-monitor environments.
- Radial Menu feature (programmable via the Control Panel) puts additional commands at user's fingertips.

## Contact info

Wacom Americas  
1311 SE Cardinal Court  
Vancouver, WA 98683  
1.360.896.9833

For more information please visit  
<http://www.wacom.com/PenDisplays>  
or email us at  
[PenDisplaySpecialist@wacom.com](mailto:PenDisplaySpecialist@wacom.com)

| General               |                                           | Display          |                                            |
|-----------------------|-------------------------------------------|------------------|--------------------------------------------|
| Dimensions            | 22.2"W x 14.7"H x 2.2"D (excluding stand) | Type             | TFT active-matrix LCD                      |
| Weight                | 16.3 lbs. (including stand)               | Screen size      | 21.5" diagonal                             |
| Data port             | USB                                       | Display area     | 18.78" x 10.56"                            |
| Graphics input/output | Analog RGB or digital DVI                 | Resolution       | 1920 x 1080 pixels (full HD)               |
| Stand adjustability   | 15° to 72° incline                        | Aspect ratio     | 16:9                                       |
| Mounting system       | VESA 100mm                                | Number of colors | 16.7 million                               |
| Pen storage           | Integrated pen holder                     | Brightness       | 200 cd/m <sup>2</sup>                      |
| Power supply input    | 100-240 VAC 50-60 Hz                      | Contrast ratio   | 700:1                                      |
| Warranty              | 2 years                                   | Work surface     | Completely flat glass, textured anti-glare |
| Tablet                |                                           | Pen              |                                            |
| Technology            | Patented electromagnetic resonance method | Type             | Pressure sensitive, cordless, battery-free |
| Active area           | 18.78" x 10.56"                           | Switches         | Tip switch, 2 side switches, eraser        |
| Resolution            | 2540 lines per inch                       | Pressure levels  | 512                                        |
| Coordinate accuracy   | +/- 0.5mm                                 | Grip             | Contoured                                  |
| Reading height        | 5 mm                                      | Tether           | 24" nylon fiber                            |