

15-inch Fanless Full Flat Touch Screen POS System

TP-2515



- **Features**

- Intel® Celeron® Bay Trail-D J1900 Processor
- Fanless Cooling System
- Modular Peripherals for Easy Installation
- Easy-Replacement Storage Drive Slot
- Water Spill Proof Front Bezel
- Slim, Sealed, and Durable Housing
- Easy Maintenance and Stylish Design

• Specifications

Model Name	TP-2515
Processor	Intel® Bay Trail-D J1900 2.0G up to 2.4G, 2M Cache
Memory	1 x DDR3L SODIMM, up to 8GB
Storage	1 x 2.5" SATA BAY (Option : m-SATA)
LCD Panel	15-inch TFT LCD with LED Backlight 1024 (W) RGB x 768 (H)
Touch Panel	True-Flat Projected Capacitive Multi Touch True-Flat 5-wire Resistive Touch
Audio	1 x 2W High Quality Speaker
I/O Expansion	
USB	4 x USB Type A (3 x USB 2.0 and 1 x USB 3.0)
LAN	1 x RJ45 10/100/1000Mbps Giga Ethernet
COM	4 x COM (DB9), w/ RI/+5V/12V
LPT	1 x DB25 Parallel Port (Option)
VGA	1 x DB-15 VGA Port
Cash Drawer	1 x RJ11 port supports 2 cash drawer with 12V or 24V by jumper
DC Power Out	1 x +12V Power Output
DC Power In	1 x Standard Mini-DIN 4PIN type
Power Management	
Power Adapter	12V@5.0A, 60W Adapter (Hide in stand)
Mechanical & Environment	
Dust and Water	IP65 on Front Panel
Tilt Adjustment	15° ~ 85 °
Dimension	356 (W) x 318 (H) x 207 (D) mm
Weight	7.1 kg
Certification	CE/FCC/LVD/BSMI/CB
Operation System	POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux
Operation Condition	0°C to +40°C / 20 to 80% without condensation (Equipped with HDD)
Storage Condition	-20°C to +55°C / 20 to 85% without condensation
Optional Peripheral	
2nd Display	9.7" (1024 x 768) LCD Display, Option : PCAP Touch Panel
Customer Display	VFD, 20 Columns x 2 Lines
MSR	Bi-directional, Comply with ISO 7811 and Three Track support
i-Button	Dallas i-button Reader
Barcode Scanner	2D CMOS Barcode Scanner
Wi-Fi	Wi-Fi IEEE 802.11 a/b/g/n/ac
VESA Bracket	VESA-Compatible, 75 x 75 (mm)